



# Factor II, Incorporated

P.O. Box 1339  
Lakeside, AZ 85929

Phone: (928) 537-8387  
Fax: (928) 537-0893

## MATERIAL SAFETY DATA SHEET

**A-564**

### Acetoxy Silicone Adhesive

In Case of Emergency Contact Factor II, Inc. 928-537-8387

Factor II Technology urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and fire prevention, as necessary or appropriate to the use and understanding of the data contained in this MSDS.

To promote safe handling each customer or recipient should: (1) notify and furnish its employees, agents, contractors, customers, and others whom it knows or believes will use this material of the information regarding hazards or safety; (2) request its customers to notify their employees, customers and other users of the product of this information.

#### 1. CHEMICAL PRODUCT

PRODUCT NAME: A-564  
CHEMICAL NAME: Reinforced Organopolysiloxane  
CHEMICAL FAMILY: Silicone  
FORMULA: Proprietary

#### 2. COMPOSITION/ INFORMATION ON INGREDIENTS

%	MATERIAL	CAS#	OSHA Hazard
100	Polyorganosiloxanes	Proprietary	N

#### 3. HAZARDS IDENTIFICATION

##### A. EMERGENCY OVERVIEW:

Physical Appearance and Odor: clear paste-like liquid, acetic acid odor-  
Warning Statements:

**CAUTION! FORMS ACETIC ACID (64-19-7) DURING CURING WHICH MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.**

##### ACUTE INGESTION

Low acute oral toxicity

##### ACUTE SKIN ABSORPTION:

Harmful if absorbed through skin. Acetic acid, emitted during curing, may cause redness, inflammation, irritation and tissue destruction.

##### ACUTE INHALATION:

Harmful if inhaled. Acetic acid, emitted during curing, may cause respiratory tract irritation.