

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT Perma-Type Surgical Cement

FILE NO.: 306
MSDS DATE: 10/11/05

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Perma-Type Surgical Cement

MANUFACTURER: The Perma-Type Company, Inc.
ADDRESS: 83 Northwest Drive
Plainville, CT 06062

EMERGENCY PHONE: (860) 747-9999
FAX: (860) 747-1986

CHEMICAL NAME: Compounded Rubber Mixture, Unvulcanized Rubber
CHEMICAL FAMILY: Polymeric
CHEMICAL FORMULA: Mixture
PRODUCT USE: Adhesive
PREPARED BY: Technical Director

SECTION 2: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT: Hexane

GAS NO.	% WT	SARA 313 REPORTABLE
110-54-3	50-80	Yes
OSHA PEL-TWA:	50 ppm	
ACGIH TLV-TWA:	50 ppm	

SECTION 2 NOTES:

SECTION 3: HAZARDS IDENTIFICATION

HMS HAZARD CLASSIFICATION
HEALTH: 1

FLAMMABILITY: 3

REACTIVITY: 0

EMERGENCY OVERVIEW: This material and its vapors are flammable. It may cause irritation.

ROUTES OF ENTRY:

POTENTIAL HEALTH EFFECTS

EYES:

Can cause redness, irritation, swelling and blurred vision.

SKIN:

Prolonged or repeated contact can cause irritation, defatting or dermatitis.

INGESTION:

Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

INHALATION:

Excessive inhalation of vapors and/or spray mist can cause respiratory irritation, dizziness, weakness, fatigue, headache, unconsciousness, even asphyxiation.

ACUTE HEALTH HAZARDS:

Irritation

CHRONIC HEALTH HAZARDS:

n/d